

PAVING IMPREGNATOR

DUALTREAT® PAVING IMPREGNATOR is a water based impregnation based on the latest nanotechnology. It can be used on all mineral surfaces such as walls, roofs and paving stones. DUALTREAT® PAVING IMPREGNATOR has a special chemical composition that reacts with mineral groups and actively bonds to building materials such as concrete, slate, etc. It protects surfaces against rain, dirt, algae, contamination, oil, grease, etc.

DUALTREAT® PAVING IMPREGNATOR is recommended for the treatment of concrete, clay, terracotta surfaces.

RECOMMENDED FOR: All mineral surfaces.

VORBEREITUNG: Apply directly on surfaces newer than 1 year. Older surfaces need to be cleaned with high pressure before the treatment. Very dirty surfaces need to be treated previously with an algae remover and rinsed with water.

APPLICATION: Apply with a low-pressure pump. Use a long-haired mop to distribute it evenly. A minimum temperature of 5°C is required for the application.

COVERAGE RATE: 100-150 ml per m² depending on surface porosity.

DILUTION: Apply undiluted

DRYING TIME: Approximately 1 hour at 20° C and 60% RH.

PACKAGING: Can 25 Liters (24 Cans/Palette).

ASPECT: Milky solution, colourless once applied.

EQUIPMENT CARE: The equipment has to be cleaned up in water directly after use.

STORAGE: Store away from direct sunlight, sources of heat and protected from frost.

SHELF LIFE: 24 months (in original sealed can).

SAFETY AND REGULATIONS: DUALTREAT® DENSIFIER is alkaline. Ensure that it does not come into contact with skin or eyes. Avoid inhalation of any air born spray. Safety glasses, gloves and rubber boots are recommended. If contact with skin occurs wash it off with clean water. If splashes into eyes occur wash immediately with plenty of clean water and seek medical advice. For detailed information regarding handling precautions please consult the safety data sheet and the product label.

HIGHLIGHTS AND PROPERTIES:

- ❖ Based on the latest nanotechnology
- ❖ Scientifically tested to protect mineral surfaces by active bonding
- ❖ Minimizes stain adherence
- ❖ Especially designed for paving stones, terrace slates and all mineral surfaces
- ❖ Extremely water repellent and self-cleaning
- ❖ Colourless
- ❖ Minimizes salt efflorescence
- ❖ Reduces the growth of moss, algae and lichen



The information contained in this documentation has been compiled in accordance with the latest technology, experience and knowledge. In view of the variety of individual projects that exist, the buyer and/or user is not released from his obligation to examine our materials to its own responsibility for the suitability for the intended use. A new datasheet replaces the information contained herein.

Last updated – January 2016